


CAUTION – RISK OF SHOCK –

Disconnect Power at the main circuit breaker panel or main fuse box before starting and during the installation.

- 1) Get item-A, mounting hardware and find the appropriate threaded holes on mounting strap. Assemble mounting screws into threaded holes.
- 2) Attach mounting strap to outlet box with the two (2) strap mounting screws.. Mounting strap can be adjusted to suit position of fixture.
- 3) Make wire connections. Reference chart below for correct connections and wire accordingly.

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)



- 5) Insert recommended bulb (not included).
- 6) Place glass up into canopy, insert and tighten the (3) C-thumb screws. (DO NOT over-tighten) Installation is now complete.

- 4) Push the B-canopy to ceiling, carefully passing mounting screws through holes, rotate canopy and tighten mounting screws.

